

C1316X
HYPERCELL

Jumper 1/2SF LSOH N Male – N Female

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF LSOH cable
Connector:	N male / N female
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	2.5 N.m Max.
Minimum Bending Radius:	25 mm

ENVIRONMENTAL

Operating Temperature Range:	-40°C < θ < + 70°C
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:		50 ± 1Ω		
Operating Frequency Range:		DC ~ 3GHz		
RMS Power (40 ℃ - 2 GHz):		0.52 KW		
Velocity:		83%		
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C1316X	310	-32	0.21	-30	0.33	-26	0.38
2	C1309X	500	-32	0.33	-30	0.49	-26	0.59
3	C1310X	690	-32	0.43	-30	0.66	-26	0.79