

# C0271F
# HYPERCELL

HPL Framework Grounding Kit

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Framework Body: | EPDM + Stainless steel |
| Grounding Cable: | Copper (0.6m length) |
| Compatibility: | Matching with the cable with copper or Aluminium outer conductor |

### MECHANICAL & ENVIRONMENTAL

| | |
|---|---|
| Color: | Black |
| Waterproof Index: | IP68 |
| RoHS Compliance: | Yes |

### ELECTRICAL

| | |
|---|---|
| Impact Current Resistance: | Grounding kit is able to bear or endure concussion current level reaching 70KA |
| Contact Resistance: | ≤ 5 mΩ |

# RANGE

| Product number | Type | Approx. weight (g / p) |
|---|---|---|
| C0275F | 1/4XF (φ6.85 × 600) | 190 |
| C1113F | 1/4F (φ6.85 × 600) | 190 |
| C0270F | 3/8XF (φ10.1 × 600) | 190 |
| C1114F | 3/8F (φ10.1 × 600) | 190 |
| C0271F | 1/2F (φ16 × 600) | 200 |
| C0272F | 7/8F (φ27 × 600) | 215 |
| C0273F | 1-1/4F (φ39.5 × 600) | 245 |
| C0274F | 1-5/8F (φ50 × 600) | 255 |