

# C1156S HYPERCELL

HPL Single Feeder Clamp

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Clamp Body: | Transnature polypropylene |
| Screw and Nut: | Stainless SUS304 |

### MECHANICAL & ENVIRONMENTAL

| | |
|---|---|
| Color: | Black |
| Use Temperature Range: | -40 °C< θ < +70 °C |
| RoHS Compliance: | Yes |

## TYPE

| Product number | Type | Approx. weight (g / p) |
|---|---|---|
| C1154S | 1 × 1/4F (φ9.5) | 155 |
| C1155S | 2 × 1/4F (φ9.5) | 190 |
| C1156S | 3 × 1/4F (φ9.5) | 210 |
| C1157S | 4 × 1/4F (φ9.5) | 240 |
| C1042S | 1 × 3/8XF (φ10.0) | 150 |
| C1173S | 2 × 3/8XF (φ10.0) | 180 |
| C1174S | 3 × 3/8XF (φ10.0) | 210 |
| C1175S | 4 × 3/8XF (φ10.0) | 240 |
| C1044S | 1 × 3/8F (φ10.6) | 168 |
| C1176S | 2 × 3/8F (φ10.6) | 187 |
| C1177S | 3 × 3/8F (φ10.6) | 206 |
| C1178S | 4 ×3/8F (φ10.6) | 225 |
| C0108S | 1 × 1/2F (φ16) | 170 |
| C0109S | 2 × 1/2F (φ16) | 190 |
| C0110S | 3 × 1/2F (φ16) | 220 |
| C0781S | 4 × 1/2F (φ16) | 240 |
| C0111S | 1 × 7/8F (φ27) | 200 |
| C0112S | 2 × 7/8F (φ27) | 250 |
| C0113S | 3 × 7/8F (φ27) | 310 |
| C0655S | 4 × 7/8F (φ27) | 360 |
| C0114S | 1 ×1-1/4F (φ39.4) | 240 |
| C0115S | 2 ×1-1/4F (φ39.4) | 340 |
| C0116S | 3 ×1-1/4F (φ39.4) | 430 |
| C0782S | 4 ×1-1/4F (φ39.4) | 515 |
| C0117S | 1 ×1-5/8F (φ50) | 280 |
| C0118S | 2 ×1-5/8F (φ50) | 400 |
| C0119S | 3 ×1-5/8F (φ50) | 505 |
| C0783S | 4 ×1-5/8F (φ50) | 620 |