

# C1037S HYPERCELL

HPL Double Feeder Clamp

## GENERAL CHARACTERISTICS

| | |
|---|---|
| Clamp Body: | Transnature polypropylene |
| Screw and Nut: | Stainless SUS304 |

### MECHANICAL & ENVIRONMENTAL

| | |
|---|---|
| Color: | Black |
| Use Temperature Range: | -40 ℃< θ < +70 ℃ |
| RoHS Compliance: | Yes |
| UV Resistance: | Pass |

# RANGE

| Product number | Type | Approx. weight (g / p) |
|---|---|---|
| C1220S | 6 × 3/8XF (φ10) | 202 |
| C1034S | 2 × 1/2F (φ16) | 160 |
| C1150S | 4 × 1/2F (φ16) | 220 |
| C0651S | 6 × 1/2F (φ16) | 250 |
| C1035S | 2 × 7/8F (φ27) | 190 |
| C1151S | 4 × 7/8F (φ27) | 260 |
| C0652S | 6 × 7/8F (φ27) | 315 |
| C1036S | 2 ×1-1/4F (φ39.4) | 245 |
| C1152S | 4 ×1-1/4F (φ39.4) | 350 |
| C0653S | 6 ×1-1/4F (φ39.4) | 450 |
| C1037S | 2 ×1-5/8F (φ50) | 260 |
| C1153S | 4 ×1-5/8F (φ50) | 390 |
| C0654S | 6 ×1-5/8F (φ50) | 510 |